

Nexus Voice

Nexus voice sounders combine normal sounder signals with a clear, synchronised voice message to help reduce confusion and distress during an active alarm.


Standard units are available with 7 pre-programmed messages. Alternative messages can be selected from an extensive message library covering almost any conceivable application. Customised messages are also available on request.

All Nexus voice sounders have a USB port that allows special messages in WAV format to be downloaded onto the sounder from any PC, providing users with the flexibility of adding/removing messages in-field.

Combined with an LED or Xenon beacon the Nexus sounder can form part of a DDA compliant system giving a clear voice message, powerful alarm tone and high output beacon for clear and effective warning.

Features

- Choice of up to 7 messages via three volt free contacts
- Message controller version also available*
- Extensive message library or bespoke messages available
- Download messages in-field via built in USB port
- 110dB (A) tone and 90dB (A) message outputs
- Automatic synchronisation
- Robust construction; IP66 rated for outdoor environments
- Volume control - 20dB
- Voltage 24V DC
- 64 tones



Specifications

Part No.	Lens Colours	Beacon Type	Sounder Current	Beacon Current
PNV-0001	-	Sounder only	30mA (max)	-
PNV-0006	Red	LED	30mA (max)	18mA/65mA**
PNV-0007	Amber	LED	30mA (max)	18mA/65mA**
PNV-0008	Green	LED	30mA (max)	18mA/65mA**
PNV-0009	Blue	LED	30mA (max)	18mA/65mA**
PNV-0010	Clear	LED	30mA (max)	18mA/65mA**
PNV-0003*	Red	LED	30mA (max)	18mA/65mA**
PNV-0011	Red	Xenon	30mA (max)	330mA@24V DC
PNV-0012	Amber	Xenon	30mA (max)	330mA@24V DC
PNV-0013	Green	Xenon	30mA (max)	330mA@24V DC
PNV-0014	Blue	Xenon	30mA (max)	330mA@24V DC
PNV-0015	Clear	Xenon	30mA (max)	330mA@24V DC

* For use with a message controller. ** Flashing/Static current consumption figures.

IP Rating: IP66 **Rating:** Continuous **Frequency:** See Tone Table

Operating Temp: -25°C to +70°C **Cable Entries:** 5

Weight: Sounder 1.1kg; Sounder Beacon 1.2kg

klaxon
Signalling Solutions