Message Controllers

When combined with a message controller voice sounders can transmit upto 4 messages over the same sounder circuit with no additional wiring.

Message Controller for Fire Alarm Systems

Alert, Evacuate, Test & All Clear messages for each stage of alarm.

Message Controller for Gas Exstinguishing Systems

Alert, Gas Release Imminent, Gas Released and Gas Hold messages for each stage of alarm.


Message controllers have two status indication LED's; a 'System Health' indicator which is green in colour and a 'fault indicator' which is amber in colour.

Features


- Acts as a communication medium between the alarm panel and voice sounders
- No additional wiring
- Fully synchronised voice messages
- System health indicators
- Simple operation
- Compatible with any of the Sonos Voice Sounders and the Nexus red LED voice sounder beacon (PNV-0003)



Fire Alarm System



Gas Extinguishing System



Specifications

	Part No.	Description	Messages	Voltage	Quiescent Current	Alarm Current	Sounder Load
	PNV-0022	Fire Alarm System	4+*	17-28V DC	16mA	45mA	2A
	PNV-0004	Gas Extinguishing Alarm System	4+*	17-28V DC	16mA	45mA	2A

IP Rating: Indoor **Operating Temp:** -10°C to +55°C **Construction:** Polycarb Flame Retardant **Weight:** 0.48Kg

Dimensions: 131mm W x 178mm H x 60.5mm D



 $^{^{}st}$ An additional default message can be played in the event of a power loss or interface fault.